


Grid LED 4000 suspended



Flood	
	97 °/76°
m	∅
1.0	2.27
2.0	4.54
3.0	6.81



A 89,4 B 80,4 C 1541 (mm)

Technical specification

Linear down light for LED tubes. Reflector with flood beam spread. Housing of powder painted sheet metal. Built in electronic.

Model and colors Available in white.

Area of use LED light for suspended Indoor applications, suitable for general lighting.

Technical data

Mains (input) voltage	220-240 V
Total weight	4,57 kg
Form of protection	IP 20, class I
Color temperature	3 000 K
Light source	LED
Operating position	Vertical
Lamp holder	NLAB Standard
Control gear	Electronic
Start time	Instant
Driver	Included
Reflector	High quality anodized reflector
Beam spreads	Flood
Design lifetime	L80 B10 50 000h

Art no	Description	Color
204-5xx	GRID LED 4000, 1541mm, 830, suspended	White
204-5xx	GRID LED 4000, 1541mm, 835, suspended	White
204-5xx	GRID LED 4000, 1541mm, 840, suspended	White

Type	Delivered lumen output (lm)	System power (W)	EEI ³
830	3834	34	A+
835	3930	34	A+
840	4027	34	A+

Note

Product also available in higher power levels. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.