



A 33,5 B 75 (mm)

Link

Technical specification

Linear led light with built in electronic gear. Housing of powder painted extruded aluminum for optimal cooling. Serial connection possible with easy Plug-in system for a continuous row of light. Link is easy and quick to install.

Model and colors Recessed or suspended. Available in black.

Area of use Linear led light for indoor applications, suitable for general or decoration lighting.

Technical data

Mains (input) voltage	220-240 V
Total weight	2.2 kg/3 kg/3.5 kg/4 kg
Form of protection	IP 20, class I
Color temperature	3 000 K
Light source	LED
Operating position	Horizontal
Start time	Instant
Driver	Built in
Optics	Opaque diffuser

Art no	Description	Color
307-500-20	L 1650mm 830	Black
307-510-20	L 2150mm 830	Black
307-520-20	L 2400mm 830	Black
307-530-20	L 2900mm 830	Black
047-xxx	Wire suspension kit	
307-211-001	Recessed bracket kit	
307-203-001	Locking device	

Type	Delivered lumen output (lm)	System power (W)	EEI ³
830 1650mm	2700	27	A+
840 1650mm	2800	27	A++
830 2150mm	3550	35	A+
840 2150mm	3650	35	A+
830 2400mm	3950	40	A+
840 2400mm	4100	40	A+
830 2900mm	4750	49	A+
840 2900mm	4950	49	A+

Note

Wire suspensions kit or recessed bracket kit is ordered separate.

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.