



LIVAL

BING PRO DL

- Rotating
- Tilting
- Light Channel
- Thermally Strong
- Reflectors: 15D, 21D, 32D
- Available Drivers: ON / OFF, Dali, Casambi

Technical data

Input Power	LED-Module	Color Consistency	Installation Type	Material	Lumen Maintenance	Luminaire Color
-------------	------------	-------------------	-------------------	----------	-------------------	-----------------

220-240V	PHILIPS-SAMSUNG-CITIZEN	2-Step MacAdam	Downlight	Powder Painted Die-Cast Aluminum	50 000h L80 B10	White (RAL 9016) Silver (Ca. RAL 9006) Black (RAL 9005)
----------	-------------------------	----------------	-----------	----------------------------------	-----------------	---

COB Type	Forward current	System Luminous Flux	System Power	Lm/W
CRI 90 3000K	250mA	1 240 lm	10,0 W	124.0
CRI 90 3000K	650mA	3 090 lm	25,4 W	121.6
CRI 90 3000K	750mA	3 519 lm	29,4 W	119.7
CRI 90 4000K	250mA	1 300 lm	10,0 W	130.0
CRI 90 4000K	650mA	3 265 lm	25,4 W	128.5
CRI 90 4000K	750mA	3 725 lm	29,4 W	126.7

