



LIVAL

First Single DL

- Tilting
- High performance
- Classic design
- Reflectors: 10D, 30D, 50D, 20D, 40D, 60D
- Available Drivers: ON/OFF, Dali, Casambi

Technical data

Input Power	LED-Module	Color Consistency	Installation Type	Installation Type	Lumen Maintenance	Luminaire Color
-------------	------------	-------------------	-------------------	-------------------	-------------------	-----------------

220 – 240V	PHILIPS – SAMSUNG – CITIZEN	2-Step MacAdam	Downlight	Power Painted Die-Cast aluminium	50 000h L80 B10	White (RAL 9016),Black (RAL 9005), Silver (Ca. RAL 9006)
------------	-----------------------------	----------------	-----------	----------------------------------	-----------------	--

COB Type	Forward current	System Luminous Flux	System Power	Lm/W
CRI 90 3000K	250mA	1 240 lm	10,0 W	124.0
CRI 90 3000K	650mA	3 090 lm	25,4 W	121.6
CRI 90 3000K	1 050ma	4 736 lm	41,8 W	113.0
CRI 90 4000K	250mA	1 300 lm	10,0 W	130.0
CRI 90 4000K	650mA	3 265 lm	25,4 W	128.5
CRI 90 4000K	1 050mA	5 030 lm	41,8 W	120.4

