



LIVAL

# Dingo

- Timeless design
- Low glare
- Reflectors: 15D, 28D, 50D
- Available Drivers: ON/OFF, Dali, Wireless Masterconnect, Casambi

## Technical data

| Input Power | LED-Module | Color Consistency | Installation Type | Material | Lumen Maintenance | Luminaire Color |
|-------------|------------|-------------------|-------------------|----------|-------------------|-----------------|
|-------------|------------|-------------------|-------------------|----------|-------------------|-----------------|

|            |                             |                |                              |                                   |                    |                                                          |
|------------|-----------------------------|----------------|------------------------------|-----------------------------------|--------------------|----------------------------------------------------------|
| 220 – 240V | PHILIPS – SAMSUNG – CITIZEN | 2-Step MacAdam | Nordic Aluminium Global Trac | Powder Painted Die-Cast aluminium | 50 000h Or 5 Years | White (RAL 9016),Black (RAL 9005), Silver (Ca. RAL 9006) |
|------------|-----------------------------|----------------|------------------------------|-----------------------------------|--------------------|----------------------------------------------------------|

| Cob Type     | Foward current | System Luminous Flux | System Power | Lm/W  |
|--------------|----------------|----------------------|--------------|-------|
| CRI 90 3000K | 350mA          | 1726 lm              | 13,9 w       | 124,0 |
| CRI 90 3000K | 650mA          | 3090 lm              | 25,4 w       | 121,6 |
| CRI 90 3000K | 850mA          | 3936 lm              | 33,7 w       | 116,8 |
| CRI 90 4000K | 350mA          | 1815 lm              | 13,9 w       | 130,6 |
| CRI 90 4000K | 650mA          | 3265 lm              | 25,4 w       | 128,5 |
| CRI 90 4000K | 850mA          | 4170 lm              | 33,7 w       | 123,7 |



