

LIVAL

SECUR 816

- Built-in Driver
- Acrylic Shade
- Reflectors: 10D, 30D, 50D, 20D, 40D, 60D
- Available Drivers: Dali, ON / OFF, Casambi



Technical data

Input Power	LED-Module	Color Consistency	Installation Type	Material	Lumen Maintenance	Luminaire Color
-------------	------------	-------------------	-------------------	----------	-------------------	-----------------

220-240V	PHILIPS-SAMSUNG-CITIZEN	2-Step MacAdam	Suspended with Power cable (3-5m)	Powder Painted Die-Cast Aluminum	50 000h L80 B10	White (RAL 9016) Silver (Ca. RAL 9006) Black (RAL 9005)
----------	-------------------------	----------------	-----------------------------------	----------------------------------	-----------------	---

COB Type 1208	Forward current	System Luminous Flux	System Power	Lm/W
CRI 90 3000K	250mA	1 240 lm	10,0 W	124.0
CRI 90 3000K	650mA	3 090 lm	25,4 W	121.6
CRI 90 3000K	1 050mA	4 736 lm	41,8 W	113.3
CRI 90 4000K	250mA	1 300 lm	10,0 W	130.0
CRI 90 4000K	650ma	3 265 lm	25,4 W	128.5
CRI 90 4000K	1 050mA	5 030lm	41,8 W	120.4



