

Standard ULTRA UHE+HE+HT

- ULTRA HIGH EFFICIENCY
- HIGH EFFICIENCY REFLECTOR
- HIGH TRANSMISSION GLASS
- IP20

Technical data

Input Power	LED-Module	Color Consistency	Installation Type	Material	Warranty	Luminaire Color	Beam Angles
220-240V	Philips 1309 UHE 930 PW Philips 1309 UHE 935 PW Philips 1309 UHE 940 PW	2-Step MacAdam	Nordic Aluminium Global Trac	Powder Painted Die-Cast Aluminum	50 000h Or 5 Years L80 B10	White (RAL 9016), Black (RAL 9005), Silver (ca RAL 9006)	15°HE 24°HE 36°HE

Forward current	COB Type	System Luminous Flux	System Power	Lm/W
200mA	1309 UHE 930 PW	1.485Lm	8,5W	174,7
300mA	2.134Lm	12,1W	12,1W	176,4
350mA	1309 UHE 930 PW	2.421Lm	14,0W	173,0
400mA	1309 UHE 930 PW	2.783Lm	16,1W	172,8
450mA	1309 UHE 930 PW	3.126Lm	18,1W	172,7
500mA	1309 UHE 930 PW	3.486Lm	20,6W	169,2
600mA	1309 UHE 930 PW	4.090Lm	24,3W	168,3
650mA	1309 UHE 930 PW	4.331Lm	26,2W	165,3



