




Spot		Medium		Flood	
18°		31°		42°	
m	ø	m	ø	m	ø
1.0	0.31	1.0	0.52	1.0	0.76
2.0	0.62	2.0	1.05	2.0	1.52
3.0	0.93	3.0	1.57	3.0	2.28



A 194 B 135 C 86 (mm)

## Zen mini 3000

### Technical specification

Track light with incorporated electronic gear and Chip on board. High quality reflectors with three different beam spreads. Lamp housing of die-cast aluminium for optimal cooling, long lifetime and low weight. Black front ring.

**Model and colors** Available in white, black and grey.

**Area of use** Track light for indoor applications.

### Technical data

Mains (input) voltage	220-240 V
Total weight	0,65 kg
Form of protection	IP 20, class I
Light source	LED
Operating position	360°/90°
Start time	Instant
Driver	Built in
Optics	Metalized aluminum reflector
Beam spreads	Spot, Medium, Flood

Art no	Description	Color
325-500-10	Spot	White
325-500-20	Spot	Black
325-500-30	Spot	Grey
325-501-10	Medium	White
325-501-20	Medium	Black
325-501-30	Medium	Grey
325-502-10	Flood	White
325-502-20	Flood	Black
325-502-30	Flood	Grey
298-317-001	Anti dazzle snoot	Black
298-210-100	Flaps kit	-
298-315-001	Honeycomb filter	-
298-314-001	Filter holder	-
236-318-103	Diffuser glass	-
236-316-103	Assymetric glass	-

Type	Delivered lumen output (lm)	System power (W)	EEI <sup>3</sup>
930	2800	24	A++
940	2800	24,5	A++
840	2900	22	A++

### Note

The above article numbers applies to 930.

Product available in other Kelvin temperatures by request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used. North American versions also available.