





| Spot | | Medium | | Flood | |
|------|------|--------|------|-------|------|
| 16° | | 28° | | 40° | |
| m | ø | m | ø | m | ø |
| 1.0 | 0.28 | 1.0 | 0.50 | 1.0 | 0.73 |
| 2.0 | 0.56 | 2.0 | 1.00 | 2.0 | 1.46 |
| 3.0 | 0.83 | 3.0 | 1.51 | 3.0 | 2.18 |



A 131 B 101 C 114 (mm)



Saw instruction: ø 124 mm

Amber mini 2500

Technical specification

Retractable and rotating down light with chip on board and separated NL Power LED electronic ballast for optimal life time and light flow performance. High quality reflectors with three different beam spreads. Lamp housing of die-cast aluminium for optimal cooling and low weight.

Model and colors Available in white, black and grey.

Area of use Down light for indoor applications.

Technical data

| | |
|-----------------------|------------------------------|
| Mains (input) voltage | 220-240 V |
| Total weight | 0,55 kg |
| Form of protection | IP 20, class III |
| Light source | LED |
| Operating position | 360°/60° |
| Start time | Instant |
| Driver | Stand alone, included |
| Optics | Metalized aluminum reflector |
| Beam spreads | Spot, Medium, Flood |

| Art no | Description | Color |
|-------------|------------------|-------|
| 296-545-10 | Spot | White |
| 296-545-20 | Spot | Black |
| 296-545-30 | Spot | Grey |
| 296-546-10 | Medium | White |
| 296-546-20 | Medium | Black |
| 296-546-30 | Medium | Grey |
| 296-547-10 | Flood | White |
| 296-547-20 | Flood | Black |
| 296-547-30 | Flood | Grey |
| 236-318-103 | Diffuser glass | - |
| 236-316-103 | Assymetric glass | - |

| Type | Delivered lumen output (lm) | System power (W) | EEI ³ |
|------|-----------------------------|------------------|------------------|
| 930 | 2400 | 23 | A+ |
| 940 | 2370 | 23 | A+ |
| 840 | 2500 | 19,5 | A++ |

Note

The above article numbers applies to 930.

Product available in other Kelvin temperatures on request. Product available with DALI option on request. Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.